

## ENGINE POWERED TELESCOPIC BOOM LIFTS

# TB38J PLUS (TB1260J PLUS)

Compliant with CE/ANSI/EAC standards

## PRODUCT HIGHLIGHTS

### Intelligent Maintenance

- Industry leading 7" screen displays faults and status information, for easy reference, reducing service technician assistance. Workers can complete tasks under the remote guidance of qualified service technicians. Convenient for fleet managers to quickly access live machine and maintenance information

### Outstanding Driving Flexibility

- Flexible maneuvering when driving, maximum extendable axles length up to 3.81m (12'6") during operation

### High Capacity

- Plus series boom lifts holds up to 1,000lb (restricted)/ 661lb (unrestricted) platform capacity allowing you to carry up to 3 occupants plus material and tools to get your job done easily

### Precision Performance

- The upper control box is equipped with 3 full-proportional handles for gradual control of boom lifting, telescoping, turntable rotation and driving speed. Operate with smooth starting and stopping and precision approach to your worksite target



Standard Features		
7-in display screen	4WD×2WS	Proportional control with 3 joysticks
Automotive-grade sleeves for all pipes	Weighing system	Hydraulic platform leveling
160° Platform rotation	Emergency stop system	Tilt protection system
Max tilt rating to 5°	Emergency lowering system	Flashing beacon
Horn & buzzer	Fault diagnosis system	Footswitch
2.44 m(8') platform	Foam-filled non-marking tires	Manual storage box
Options & Accessories		
AC power to platform	Solid tires	1.45 m (4'9") platform
1.83 m(6') work platform	1.83 m(6') /2.44m(8') platform with swinging gate	Platform work light
Glazier kit(For platform with swinging gate)	Half mesh (For platform with swinging gate)	Telematics-ready connector
Secondary guarding device	Overhead anti-collision device	

**SINOBOOM™**

**PARTNERS IN ACCESS™**

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

# ENGINE POWERED TELESCOPIC BOOM LIFTS TB38J PLUS (TB1260J PLUS)

Compliant with CE/ANSI/EAC standards

Model	TB38J Plus (TB1260J Plus)
<b>Dimensions</b>	
Max Platform Height	38.4 m (126')
Max Working Height	40.4 m (132'6")
Max Horizontal Reach(Restricted/Unrestricted)	19.5 m/21 m (63'11"/68'11")
A Stowed Length	13.8 m (45'3")
B Stowed Width (Axle Retracted/Axle Extended)	2.49 m/3.36 m (8'2"/11')
C Stowed Height	3.1 m (10'2")
Stowed Length (Transport)	12.3 m (40'4")
Stowed Width (Transport)	2.49 m (8'2")
Stowed Height (Transport)	3.1 m (10'2")
D Wheelbase	3.66 m (12')
Ground Clearance	0.43 m (1'5")
Platform Size (L×W×H)	2.44×0.91×1.1 m (8'×3'×3'7")
<b>Performance</b>	
Max Platform Capacity(Restricted/Unrestricted)	454 kg/300 kg (1,000lbs/661lbs)
Max Platform Occupants(Restricted/Unrestricted)	3 persons/ 2 persons
Drive Speed (Stowed)	0~4.4 km/h (0~2.75 mph)
Drive Speed (Raised)	0~1.1 km/h (0~0.68 mph)
Gradeability	40%
Turntable Rotation	360°/Continuous
Platform Rotation	160°
Tilt Rating	5°
Turning Radius (Inside/Outside)	2.56 m/5.57 m (8'4"/18'3")
Turntable Tail-Swing	1.86 m (5'11")
Max Allowable Side Force	400 N (90 lbf)
Max Allowable Wind Speed	12.5 m/s (28 mph)
Tire Spec/Type	385/65D22.5 (Foam-filled)
<b>Power</b>	
Drive × Steer	4WD × 4WS
Engine	54 kW/2400 rpm/ QSF2.8t3TC72/Cummins/China T3
Hydraulic Tank Capacity	260 L (57.2 gal(UK)/68.7 gal(US))
Diesel Tank Capacity	200 L (44.0 gal(UK)/52.8 gal(US))
System Voltage	12 VDC
<b>Weight</b>	
Weight	20,700 kg(45,635 lbs)
Standards Compliance	CE/ANSI/EAC

